


PURe® SLIDE lift & slide aluminium door system by **euro**sash



The PURe® SLIDE lift & slide door has been designed to meet current and future building regulation, with impressive U values and thermal performances. PURe® systems combine the long life and low maintenance of powder coated aluminium, with a patent pending high insulation PUR foam thermal barrier.

Available in Twin Track or Triple Track Options

- Aluminium sections extruded using Aluminium Alloy 6060 or 6063 T6 to BS EN 755 part 9 2008 or BS EN 12020-2.
- Polyamide thermal barriers are manufactured in accordance with PA66 GF25.
- Polyester Powder Coating to BS EN 12206:2004 Part 1 –painted in house, surface finish enhanced to 60 microns for marine grade environments.

Weather Rating

Tested to BS6375-1, BS6375-2 and BS6375-3

Sizes & Weights

Max Door Leaf Width	3005mm
Max Door Leaf Height	2916mm
Max Outerframe Width	Project Specific
Max Outerframe Height	3000mm
Max Weight Per Door Leaf (Standard Duty)	200Kg
Max Weight Per Door Leaf (Heavy Duty)	300Kg

Typical U-Values

28mm Double Glazed Unit	1.48 W/m ² K
48mm Triple Glazed Unit	1.11 W/m ² K
Glazing Thickness from 28mm to 52mm	

Security

Security tested to PAS24: 2012 (with security hardware)